

## Technical Data Sheet

# B8118

Fabric / Weefsel / Tissu / Gewebe	100 % PES / 1100 dtex	
Total weight / Gewicht totaal / Poids total / Totalgewicht	850 g/m <sup>2</sup>	DIN EN ISO 2286/2 1998
Embossing / Kalander / Calandre / Lackierung	CUBE	
Characteristics Eigenschappen Caractéristiques Eigenschaften	ABUV / SOP	
Lacquering / Vernis / Lackierung	1/1	
Breaking strength Warp Treksterkte Ketting Résistance rupture Chaîne Höchstzugkraft Kette	2500 N/5cm	EN ISO 1421/1 1998
Breaking strength Weft Treksterkte Inslag Résistance rupture Trame Höchstzugkraft Schuss	2300 N/5cm	EN ISO 1421/1 1998
Tear strength Warp Scheurweerstand Ketting Résistance à la déchirure Chaîne Weiterreisskraft Kette	270 N	DIN 53363 2003
Tear strength Weft Scheurweerstand Inslag Résistance à la déchirure Trame Weiterreisskraft Schuss	270 N	DIN 53363 2003
Adhesion / Hechting / Adhérence / Haftung	100 N/5cm	EN ISO 2411 2000
Temperature resistance / Temperatuursbestendigheid / Tenue à la température / Temperatuursbeständigkeit	-30/+70 °C	DIN EN 1876/2 1998

"This product may for certain colours contain substances (Lead Pigments) which fall under the Annex XIV of the Reach Regulation 1907/2006/CE.  
In order to know which colours fall under this annex, you can take contact with the technical department of Sioen Industries.  
Upon request those substances can be eliminated from the product."

Technical Data Sheet

## B8118

Light fastness (Except white and (half-)transparent)	7-8	ISO 105 B02 2014
Lichtechtheid (Uitgezonderd wit en (half-)transparent)		
Tenue à la lumière (Excepté en blanc et (semi-)transparent)		
Lichtechtheid (Ausnahme weiss und (semi-)transparent)		
Fire behavior / Brandgedrag / Reaction au feu / Brennverhalten	M2	NF P 92 507 2004
Application -> Tent&TA/BlockOut		



*"This product may for certain colours contain substances (Lead Pigments ) which fall under the Annex XIV of the Reach Regulation 1907/2006/CE.  
 In order to know which colours fall under this annex , you can take contact with the technical department of Sioen Industries.  
 Upon request those substances can be eliminated from the product."*